

PORCELAIN PAVING ENHANCER ECO/27



SEAL & PROTECT

WATER BASED SELF-SHINE ENHANCER

For Porcelain Paving. Exterior & Interior Use.
A low maintenance film forming surface sealer & protector. Enhances and embellishes the appearance. Highly resistant to wear and stains. Facilitates maintenance and cleaning.
Leaves surfaces with a 'just washed' look.

DIRECTIONS FOR USE

Preparation:

Newly installed surfaces - Ensure surface to be treated is completely clean, dry, and free from dirt, grime, cement, and grout. (see ECOPROTEC Cement, grout & Salt Remover).

Existing surfaces - First clean and degrease surfaces with ECOPROTEC Intensive Cleaner. Rinse well. Leave to dry out thoroughly (24 hrs)

Application:

Clean and dry surface - Apply using a foam roller, sealant applicator pad or paint brush. Pour contents into a separate container or dip tray. Apply to the surface without rubbing until an evenly thin film is created. Allow to dry (1 hr). For a more enhanced appearance further coats should be applied at right angles to the first (max.4.)

Do not over apply as a heavy layer or too many coats may cause unsightly build up/affect slip resistance and/or reduce the efficiency of product. Hardens after about an hour but will take a further three days to achieve full hardness and become fully resistant. Always test first to establish the correct method of application and optimum number of coats before general use.

Avoid extremes of temperature. Surface temperature range for application between 5°C - 25°C

COVERAGE: M ² PER COAT	1 LTR	5 LTR
Lower porosity surfaces	30-40 m ²	150-200 m ²

AFTERCARE

Routinely sweep and wash surfaces. Clean and mop surfaces with ECOPROTEC General Cleaner. At some stage (every 2-3 years) complete renovation of the Porcelain Paving Enhancer may be desired. In this case use ECOPROTEC Joint Residue Remover to strip the original coatings before re-applying. Regular cleaning with steam cleaners, jet washers and strong detergents should be avoided.

INFORMATION

Store in a cool, dry, frost-free environment. Store locked up. Shelf Life – Up to 2 years for un-opened containers. Do not use in temperatures under 5°C or over 25°C. Clean application tools and brushes with water after use.

HEALTH, SAFETY & ENVIRONMENTAL

Keep out of reach of children.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents/container in accordance with national regulations.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.